

#### SECTION 1: Product and Company Identification

Product Name: GSL-LU1

Recommended Use: Flexible Shaft Lubricant

**Distributor Information:** 

Goodway Technologies Corp. Phone: (203) 359.4708
420 West Avenue Emergency Number (24 hours):
Stamford, CT 06902 CHEMTREC 800-424-9300

# **SECTION 2: Hazards Identification**

GHS Classification: Sensitization, skin: Category 1, H317

Carcinogenicity: Category 2, H 351

GHS Label Elements:

 $\Diamond$ 

Signal Word: Warning

**Hazard Statements:** 

H317 May cause an allergic skin reaction H351 Suspected of causing cancer

# **Precautionary Statements**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

### **SECTION 3: Composition/Information on Ingredients**

Chemical Name	CAS#	%
ethanolamine	102-71-6	5-10
Diethanolamine	111-42-2	<0.1

Note: Triethanolamine is neutralized with fatty acids to form alkanolamide soaps

#### **SECTION 4: First Aid Measures**

#### General

Contaminated individuals of chemical exposure must be taken for medical attention if any adverse effects occur. When possible bring along copy of label and SDS to health professional.

Inhalation: May cause mild respiratory tract irritation. Remove individual to fresh air. If breathing

is difficult give oxygen.

Skin Contact: Flush the affected area with water for 15 minutes minimum. Remove exposed or

contaminated clothing and shoes. Wash contaminated clothing before reuse. Seek

medical attention if irritation persists.

Eye Contact: Remove contact lenses if present. Rinse eyes thoroughly with water for 15 minutes

minimum. Seek medical attention immediately.

Ingestion: If conscious give one cup of water or milk if available and transport to a medical

facility. Do not give anything by mouth to an unconscious person.

Most important symptoms

acute or delayed: Not available

Recommendations for immediate medical

care and special treatment: Not available

### SECTION 5: Fire Fighting Measures

Suitable extinguishing media: Carbon dioxide, extinguishing powder or water spray.

Unsuitable extinguishing media: Not available

Specific hazards arising

during fire:

Combustion may generate carbon monoxide, carbon dioxide, oxides of nitrogen

Firefighting equipment: Firefighters should wear suitable protective equipment

Firefighting instructions: Evacuate personnel to a safe area. Firefighters should use self-contained breathing

equipment and protective clothing. Keep containers cool with water spray.

#### SECTION 6: Accidental Release Measures

**Personal Precautions:** Wear appropriate protective equipment and clothing during clean up. Keep

unprotected persons away.

**Environmental Precautions** Do not allow product to enter sewers, surface or ground waters.

Methods and materials for containment and cleanup: Contain and recover liquid when possible. Absorb with suitable absorbent and

in a chemical waste container for proper disposal (see Section 13, Disposal

Considerations).

### SECTION 7: Handling and Storage

Precautions for safe handling: As with all chemical products, avoid contact and wash thoroughly after handling.

Do not eat, drink or smoke while using this product. Use only in well-ventilated areas. Remove contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage including incompatibilites:

All personnel who handle this product should be trained in its safe handling. Store tightly closed in cool, dry, ventilated area. Keep out of direct sunlight and away from

heat and incompatible materials. Avoid contact with acids, oxidizing agents, and caustics and nitrites.

WARNING: Do not mix with sodium nitrite or any nitrosating agent as potentially

carcinogenic nitrosamines may be formed.

# SECTION 8: Exposure Controls/Personal Protection

#### **Exposure limit values**

Material	CAS#	List	Type	Value
Triethanolamine	102-71-6	ACGIH	TWA	5 mg/m3
N,N-Diethanolamine	111-42-2	ACGIH	TWA	5 mg/m3
		NIOSH	REL	3 ppm (15mg/m3)
		ACGIH	TWA	1 mg/m3

Provide sufficient mechanical (general/and or local exhaust) ventilation to maintain Appropriate Engineering Controls:

exposure below exposure guidelines, if applicable, or below levels that cause known,

suspected, or adverse effects.

Personal Protective Measures

Eye/face protection: Use chemical goggles or full face shield.

Use chemically-resistant gloves.

Hand protection: Respiratory:

Not required under normal conditions of use. If airborne concentrations exceed

applicable exposure limits, use NIOSH approved respiratory protection.

Not available Thermal hazards:

Handle in accordance with good industrial hygiene and safety practice. Eyewash station and General hygiene considerations:

safetv shower should be in vicinity of work area.

# **SECTION 9: Physical and Chemical Properties**

Appearance: Bluish-green liquid

Odor: Faint
Odor threshold: Not available

pH (5%soln): 7.6
Solubility in water: Soluble
Viscosity: Not available

Specific gravity: 1.03

Melting point:

Not available
Freezing point:

Not available

Initial boiling point

and boiling range:

Flash point:

Evaporation rate:

Flammability (solid, gas):

Upper/Lower flammability or explosive limits (%)

Flammability limit-lower:

Not available

Flammability limit-lower: Not available
Flammability limit-upper: Not available
Explosive limit-lower: Not available
Explosive limit-upper: Not available
ure Not available

Vapor pressure Not available Vapor density Not available

Partition coefficient

 (octanol:water)
 Not available

 Auto-ignition temperature
 Not available

 Decomposition temperature
 Not available

#### SECTION 10: Stability and Reactivity

Reactivity: No reactivity hazards are known.

**Chemical Stability:** Material is stable under normal conditions of storage and handling.

Possibility of No hazardous reactions are known under normal conditions of use.

hazardous reactions:

Conditions to avoid: Keep away from heat, sparks, open flames. Protect from freezing.

Materials to avoid: Keep away from incompatible materials (strong acids, oxidizing agents, caustics)

and nitrites.

Hazardous decomposition May include carbon monoxide, carbon dioxide, oxides of nitrogen

### **SECTION 11: Toxicological Information**

#### Acute Toxicity:

Triethanolamine

Ingestion LD50, rat, 6400 mg/kg

Dermal LD 50, rabbit, greater than 2000 mg/kg

**Skin:** May cause skin irritation. May cause allergic skin r e a c t i o n .

Eyes: May cause eye irritation.

Inhalation:May cause mild irritation of the respiratory tract with prolonged exposure.Ingestion:May cause moderate to severe irritation of the mouth, throat and stomach.

Delayed and immediate

effects of exposure: Not available.

Carcinogenicity:Product contains traces of Diethanolamine (111-42-2):IARC:N,N-Diethanolamine: Possibly carcinogenic to humans, 2B

ACGIH: N,N-Diethanolamine: Confirmed animal carcinogen with unknown relevance

**SECTION 12: Ecological Information** 

**Ecotoxicity:** The product is not classified as environmentally hazardous.

Triethanolamine and fatty acid components are biodegradable

Bioaccumulation potential: Not available.

Mobility: Not available.

Other adverse effects:

Not available.

**SECTION 13: Disposal Considerations** 

Disposal instructions: Waste disposal must be in accordance with appropriate US Federal, State

And local regulations.

**Disposal of contaminated**Dispose of as unused product.

containers or packaging:

**SECTION 14: Transportation Information** 

UN Number: Not regulated

**UN proper shipping name:** Compounds, cleaning liquids, not regulated

Transport hazard class: Not regulated Packing group: Not regulated

Marine pollutant: No

SECTION 15: Regulatory Information

Toxic Substances Control Act All components of this product are on the TSCA Inventory or are exempt from

NO

(TSCA): reporting requirements.

SARA 302 Extremely Hazardous Substances:

SARA 311/312 Classification:

Immediate hazard

Delayed hazardNoFire hazardNoReactive hazardNoPressure hazardNo

SARA 313 Components: Diethanolamine RQ=100 lb

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This product contains a chemical known to the State of California to cause cancer

Component CAS# Amou

N,N-Diethanolamine 111-42-2 < 0.1%

**HMIS Information:** 

Health	1
Flammability	0
Reactivity	0
Personal Protection	В



# **SECTION 16: Other Information**

**Disclaimer:** Goodway Technologies Corporation products are manufactured for professional and industrial use only.

Goodway Technologies Corporation believes the information contained herein is valid and accurate and makes no representation or warranty, express or implied, including the warranties of merchantability and

fitness, for a particular purpose with respect to the information contained herein.

Last Revision: July 9, 2015