

# TOP TOOLS FOR PLUGGED TUBES



## ADJUSTABLE SILICONE TUBE PLUGS:

Designed not to damage tube walls and to conform to almost any inside tube surface, these adjustable tube plugs provide a versatile option when tubes must be plugged. Brass or stainless steel nuts and bolts, vulcanized silicone rubber and high-performance plastic make materials compatibility a non-issue. Available in single seal configurations for lower pressure applications (less than 60 PSI) or double seal configurations for higher pressure applications (up to 150 PSI), these plugs are designed for long-life at high temperatures, in fresh or salt water. Removal is also easy. Pre-set torque wrenches make proper installation fool-proof. They are manufactured in sizes to cover chiller and heat exchanger tubes 5/8", 3/4", 7/8", 1", 1 1/8" or 1 1/4" O.D. with BWG ranges 18-25.

**TP-ADJ-B:** Adjustable silicone tube plug with brass nuts and bolt .....  
**Call for Prices and Quantity Discounts**

**TP-ADJ-S:** Adjustable silicone tube plug with stainless steel nuts and bolt  
**Call for Prices and Quantity Discounts**

**TP-ADJ-TW-SM:** T-Handle Torque Wrench for 5/8" to 3/4" O.D. plugs,  
 preset to 17 in. lbs. ....**Call for Price**

**TP-ADJ-TW-LG:** T-Handle Torque Wrench for 7/8" to 1 1/4" O.D. plugs,  
 preset to 33 in. lbs. ....**Call for Price**

**Note:** Additional style and size Tube Plugs available.

## ADJUSTABLE TUBE PLUG WITH BRASS HARDWARE FOR 3/4"-16 GA TUBES (5/8"ID):

**TP-075-16D-B:** Adjustable tube plug with double seal and brass hardware for 3/4" - 16 ga tubes (5/8" ID) .....**Call for Price**

**TP-075-16S-B:** Adjustable tube plug with single seal and brass hardware for 3/4" - 16 ga tubes (5/8" ID) .....**Call for Price**

## BRASS TUBE PLUGS:

Got a leaky tube? Plug it with the original solution that always works, a one-piece tapered brass tube plug. When installed properly, tapered brass tube plugs can stay in place for years. Precision engineered, Goodway Brass Tube Plugs are ideal for a wide range of tube applications, and should be driven into the tube with a hammer just far enough to form a seal. They are manufactured in sizes to cover chiller and heat exchanger tubes 5/8", 3/4", 7/8" or 1" O.D. with BWG ranges 15-22.

**TP-062S:** Brass Tube Plug for tubes  
 5/8" O.D. with BWG ranges 15-22 .....**Call for Price**

**TP-075S:** Brass Tube Plug for tubes  
 3/4" O.D. with BWG ranges 15-22 .....**Call for Price**

**TP-087S:** Brass Tube Plug for tubes  
 7/8" O.D. with BWG ranges 15-22 .....**Call for Price**

**TP-100S:** Brass Tube Plug for tubes  
 1" O.D. with BWG ranges 15-22 .....**Call for Price**

**Note:** Additional style and size Tube Plugs available.

	TP-062S	TP-075S	TP-087S	TP-100S
OD	5/8"	3/4"	7/8"	1"
BWG Range	15-22	15-22	15-22	15-22
ID	0.481"- 0.569"	0.606"- 0.694"	0.731"- 0.819"	0.854"- 0.944"

## TUBE ID SIZES

BWG	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wall Thickness	0.109	0.095	0.083	0.072	0.065	0.058	0.049	0.042	0.035	0.032	0.028	0.025	0.022	0.020
Outside	Inside													
1/4"	0.032	0.060	0.084	0.106	0.120	0.134	0.152	0.166	0.180	0.186	0.194	0.200	0.206	0.210
3/8"	0.175	0.185	0.209	0.231	0.245	0.259	0.277	0.291	0.305	0.311	0.319	0.325	0.331	0.335
1/2"	0.282	0.310	0.334	0.356	0.370	0.384	0.402	0.416	0.430	0.436	0.444	0.450	0.456	0.460
5/8"	0.407	0.435	0.459	0.481	0.495	0.509	0.527	0.541	0.555	0.561	0.569	0.575	0.581	0.585
3/4"	0.532	0.560	0.584	0.606	0.620	0.634	0.652	0.666	0.680	0.686	0.694	0.700	0.706	0.710
7/8"	0.657	0.685	0.709	0.731	0.745	0.759	0.777	0.791	0.805	0.811	0.819	0.825	0.831	0.835
1"	0.782	0.810	0.834	0.854	0.870	0.884	0.902	0.916	0.930	0.936	0.944	0.950	0.956	0.960

**GOODWAY®**  
 INNOVATIVE MAINTENANCE SOLUTIONS

**Call: 1-800-333-7467**  
**Visit: [www.goodway.com](http://www.goodway.com)**

Goodway Technologies Corporation  
 420 West Avenue, Stamford, CT 06902-6384 U.S.A.  
 Phone: 203-359-4708 • Fax: 203-359-9601 • [goodway@goodway.com](mailto:goodway@goodway.com)