## **TOOLS** FOR BASIC **MAINTENANCE AND REPAIR**



# **PSM-500 – Easy Handling**

Small, straight tubes can often be the source of some not so straight forward problems. Tubes measuring 1" I.D. and smaller can easily trap debris or become clogged from just a minor buildup of deposits. Fortunately, with the PSM-500 Tube Cleaning Drill an in-line water flush makes easy work of removing a wide range of debris, from solid clogs to soft deposits. After just one cleaning with the PSM-500, you'll be amazed at how easy it is to maintain an optimal tube condition in all of your straight, small tubes.





### **RECOMMENDED:**

For better air regulation and quality, plus longer motor life, we recommend the combination air lubricator, filter and regulator unit.

**GTC-705-4:** Combination Air Lubricator, Filter and Regulator (see goodway.com) Call for Price

### **OPTIONAL:**

#### **FEATURES**

- Compact, rugged construction
- Independent air motor and water flow controls to reduce water consumption
- Push button trigger to reduce fatigue



PSM-500	
Motor Power	Up to 0.7 HP depending on air pressure and volume
Air Requirements	Minimum 50 PSI at 10.6 CFM, Maximum 90 PSI at 19 CFM
Drill Speed	950 rpm (free speed)
Water Requirements	Minimum 30 PSI at 2 GPM, Maximum 100 PSI at 2 GPM
Hoses	15' air hose and 15' water hose
Dimensions	11 1/4" long
Weight	5 1/2 lbs net dry
Optional Carrying Case	14" high x 53 1/2" wide x 43/4" deep



Call: 1-800-333-7467 Visit: www.goodway.com

**Goodway Technologies Corporation** 

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com