

EVERY HVAC TECHNICIAN NEEDS TUBEGUARD-XL



1

CLEAN

Variable shaft speed has a reversible shaft rotation and simultaneously flushes TubeGuard-XL chemical

2

DISINFECT

TubeGuard-XL tablet eliminates biofilm

3

PROTECT

TubeGuard-XL tablet prevents corrosion

CUSTOMER FAVORITE

RAM PRO XL® – It's A Game Changer!

The cutting-edge in chiller tube cleaning technology, RAM PRO XL® combines the best in rotary tube cleaning mechanics with TubeGuard technology. TubeGuard is an advanced cleaning system with a hospital-grade disinfectant that blasts biofilm and protects against corrosion. For cleaner, more efficient tubes, it's as easy as 1, 2, 3.



BLAST BIO-FILM AND PROTECT TUBES WITH TUBEGUARD-XL!

TUBEGUARD-XL-4: Package of four tube cleaning tablets (for three average sized chiller cleanings). For use with the RAM PRO XL®

Call for Price

FEATURES

- On-board TubeGuard dispensing system
- Heavy-duty roll cage construction with integrated dolly
- 0.5HP motor
- Quick connect threadless shaft manifold
- Direct drive
- Interchangeable cleaning tools
- Variable shaft speed
- Reversible shaft rotation
- Simultaneous water flush
- Power cord and foot pedal storage

Get Your Brushes & Flexible Shafts from the Best in the Industry

GTC-703Q-25:
25' Flexible Shaft
GTC-211Q-5/8:
5/8" Blue Nylon Brush



U.S. PATENT NO. D722,737

HOW MUCH TUBEGUARD-XL DO I NEED?

Two tablets for every 200-250 tubes in tube cleaning applications with a RAM PRO XL®.

RAM-PRO-XL-60: Tube cleaner w/ quick connect manifold, integrated roll cage/dolly, two direction foot switch (115V 50/60 Hz), and a four pack of TubeGuard-XL Tablets **Call for Price**

RAM-PRO-XL-A: (230V 50/60 Hz) **Call for Price**

Note: Visit Goodway.com for shafts and accessories.

RAM PRO XL	
Motor Power	Standard: 0.5 HP (90 VDC)
Input Power	Standard: 5.5 amps, 115V, 50/60 Hz AC Optional: 3 amps, 230V, 50/60 Hz AC
Power Supply Cord	21', 14-3 GFCI
Flexible Shaft Speed	Variable 0-900 rpm
Water Requirements	Minimum 30 PSI at 2 GP
Dimensions	20" high x 16" wide x 26" deep
Weight	55 lbs net dry

GOODWAY®
INNOVATIVE MAINTENANCE SOLUTIONS

Call: 1-800-333-7467

Visit: www.goodway.com

Goodway Technologies Corporation

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com