

# DOUBLE YOUR PERFORMANCE

## WITH TWIN MOTORS



### VAC-2 – Increased Suction

The VAC-2 features dual-motors for increased suction. Its power and versatility make it an ideal choice for a wide range of general shop cleanup tasks, from liquid recovery to picking up metal shavings. With specially designed adapter rings, the VAC-2 is compatible with 15 gallon tanks or with 30 or 55 gallon drums to suit the size of the cleanup jobs you encounter.

A wide array of options and configurations are also available to suit your unique applications.

#### FEATURES

- Two heavy-duty motors
- Exhaust muffler
- Three tank sizes
- Liquid shut-off
- Metal deflector
- Reusable filters
- 1 1/2" or 2" hoses

#### ACCESSORIES:

**VAC-KIT-9:** 1 1/2" Industrial Vacuum Accessory Kit: 10' Neoprene Wire Reinforced Hose, 54" Double Bend Wand, 54" Extension Tube, 5' Extension Tube, 14" Nylon Floor Brush, 14" Squeegee Floor Tool, 14" Rough Surface Fiber Shod Floor Tool, 8" Wall and Overhead Brush, and 27" Steel Crevice Tool.....**Call for Price**

#### DUMP VALVE (FACTORY INSTALLED):

**DDV-100M:** Full Flow Ball Valve, 1".....**Call for Price**

**DDV-E90:** Elbow, 90°.....**Call for Price**

**DDV-675:** Garden Hose Connector .....**Call for Price**

#### STORAGE POUCH:

**VAC-TOOL-TOTE:** Durabond Tool Storage Pouch **Call for Price**

#### REPLACEMENT FILTERS:

**GTC-175:** Polypropylene Filter, 15 microns .....**Call for Price**

**GTC-176:** Dacron Filter, 15 microns .....**Call for Price**

#### DISCHARGE PUMP:

The VAC-2-55-DD Industrial Vacuum is available with a 1/3 HP, 45 GPM, stainless steel internal pump for discharging recovered liquids.

**VAC-2-55-PUMP:** Same as VAC-2-55-DD, plus internal pump, discharge port and hose.....**Call for Price**



**VAC-2-15SS:** Industrial Wet-Dry Vacuum, including filters, 15 gallon stainless steel tank, handles, wheels and casters....**Call for Price**

**VAC-2-30\*:** Industrial Wet-Dry Vacuum, including filters and 18"-20" diameter drum adapter ring (no drum).....**Call for Price**

**VAC-2-30DD:** Same as VAC-2-30, plus 30 gallon bonderized steel drum and dolly.....**Call for Price**

**VAC-2-55\*:** Industrial Wet-Dry Vacuum, including filters and 22"-24" diameter drum adapter ring (no drum).....**Call for Price**

**VAC-2-55DD:** Same as VAC-2-55, plus 55 gallon bonderized steel drum and dolly.....**Call for Price**

**\*Note:** Fits any standard drum 30 or 55 gallon depending on model.

**Note:** Vacuums do not include accessories. Order VAC-KIT-9, also shown on page 153, or individual accessories shown on pages 152-160.

VAC-2	
Motor Power	2.7 HP (total)
Input Power	Standard: 13 amps, 115V, 50/60 Hz AC Optional: 6.5 amps, 230V, 50/60 Hz
Power Supply Cord	37', 14-3
Static Water Lift	66"
Air Displacement	180 CFM
Filtration	15 microns polypropylene and 15 microns dacron
Tank/Drum	15 gallons stainless steel tank, or 30 or 55 gallons bonderized steel drum
Dry Capacity	14 gallons (stainless steel tank)
Wet Capacity	10 gallons (stainless steel tank)
Noise Level	74 dBA
Dimensions	15" diameter tank x 36" high (VAC-2-15SS)
Weight	25 lbs (head only) and 66 lbs (VAC-2-15SS)