

# SAFETY IS FIRST WITH THIS EXPLOSION PROOF VACUUM



NEW & IMPROVED -  
LARGER TANK!



II 2G Ex g IIB T6 Gb  
II 2D Ex h IIIC T85°C Db

## DESIGNED FOR USE IN HAZARDOUS LOCATIONS:

- Class I, Division 2 Groups A, B, C & D
- Class II, Division 2 Groups F & G

## FEATURES

- Air-powered
- Detachable roll-out collection tank
- External filter shaker
- Reusable pocket filter
- Tool basket

## DV-AV-EP – State of the Art

Plants and facilities that contain flammable, combustible or hazardous materials require special equipment. With the Air-Powered DV-AV-EP Dry Vacuum, you will be fully prepared should you encounter such situations.

Risk-free operation is assured with a non-sparking stainless steel tank and anti-static 1 micron pocket filter. An external filter shaker saves time by keeping the filters clear so you don't have to, and a detachable collection tank enables you to empty its contents with minimal time and effort.

**DV-AV-EP:** Air-powered Dry Explosion Proof Vacuum, including grounding cable, anti-static filter, external filter shaker, 27 gallon non-sparking stainless steel detachable tank, handles, casters and tool basket

**Call for Customization Options and Price**

**Note:** Vacuum does not include accessories. Order DA-EP-KIT.

## GROUNDING AIR SUPPLY HOSE:

**DV-AH-50:** Grounded Air Supply Hose, 1/2" I.D. x 50' **Call for Price**

## REPLACEMENT FILTER:

**DA-AH-PF:** Anti-Static Pocket Filter, 1 micron **Call for Price**

## DID YOU KNOW?

- Many materials can become combustible when they become powdered.
- Speak to your safety manager before purchasing vacuums.
- Before purchasing, match your specific material pickup needs to specific NEC divisions and classes.

Learn more about industrial vacuums at  
[www.goodway.com](http://www.goodway.com)

## DV-AV-EP

Air Requirements	Minimum 50 PSI at 35 CFM, Maximum 90 PSI at 50 CFM
Air Line	1/2" I.D. or larger
Static Water Lift	160" at 90 PSI
Air Displacement	125 CFM at 90 PSI
Filtration	1 micron anti-static pocket
Tank	27 gallons stainless steel
Dry Capacity	23 gallons
Noise Level	74 dBA
Dimensions	20 1/2" diameter tank x 64" high
Weight	132 lbs

**GOODWAY®**  
INNOVATIVE MAINTENANCE SOLUTIONS

**Call: 1-800-333-7467**

**Visit: [www.goodway.com](http://www.goodway.com)**

**Goodway Technologies Corporation**

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • [goodway@goodway.com](mailto:goodway@goodway.com)