

SEMI-AUTOMATED DESCALING SYSTEM



RECOMMENDED CLEANER
ScaleBreak-5
 Find on pages 46, 167

U.S. PATENT NOS.
 10,012,455, 8,926,765



FEATURES

- Acid proof pump and fittings
- On-board pH level monitor
- 30 GPM pump recirculates quickly
- Easy to understand control panel monitors progress
- Multiple valves and input allow for immersion tank recirculating
- 15 gallon venting drum for closed systems
- Hands-free automatic chemical pump

APPLICATIONS

- Boilers and hot water heaters
- Steam generators
- All types of heat exchangers
- Condensers and chillers
- Cooling coils and water-cooled rolls
- Coolers, mold tools, and extruder barrels found on injection molding machines

GDS-15-PH – Scale Buster

The GDS-15-pH is a medium range clean-in-place (CIP) pump system with 30gpm capability and ample flow through the 1-1/2" pump and hoses. The GDS-15-pH blazed a trail in CIP pump systems designs by incorporating a pH meter for continuous measurements as well as its integrated chemical drawing system.

When you start out with your initial recommended amount of ScaleBreak, the on-board suction system pulls in additional descaler if needed as the pH value rises. The GDS-15-pH is constructed with acid resistant materials and is vertically positioned to fit in tight work spaces. The ergonomic upright design allows for easy movement. This medium range pump system is perfect for condenser barrels on chillers ranging from 100 - 500 tonnage ratings.

GDS-15-PH: Scale Removal System, including two 15' circulation hoses, 15 gallon venting drum, pH probe, 1 pint pH probe storage solution, five pH 7.01 calibration packets and five 4.01 pH calibration packets **Call for Price**

GDS-15-PH

Motor Power	3/4 HP
Input Power	Standard: 11 amps, 115V, 60 Hz AC Optional: 5.5 amps, 230V, 50 Hz
Power Supply Cord	21', 14-3
Output Water Press./Flow	30 feet of head at 30 GPM
Pumps	Noryl centrifugal main pump and positive displacement diaphragm chemical pump
Venting Drum	15 gallons
Dimensions	48" high x 26" wide x 33" deep
Weight	125 lbs net dry

GOODWAY[®]
 INNOVATIVE MAINTENANCE SOLUTIONS

Call: 1-800-333-7467

Visit: www.goodway.com

Goodway Technologies Corporation

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com