CLEANER TOWERS WITH ZERO DOWNTIME



CTV-1501 TowerVac® – Efficiency with No Hassles

Safely remove cooling tower sediment sludge without having to drain or shut down the system. This award-winning product features an adjustable flow control that allows you to vacuum at a recovery rate of up to 60 GPM.

Easily remove slime, algae, mud, and other contaminants from the sides and floor of any cooling tower basin or sump. Stop dirty cooling tower water from fouling chillers, robbing efficiency, and increasing energy costs.

FEATURES

- Stainless steel construction
- Heavy-duty motor removes up to 60 gallons of water and debris per minute
- Semi-automatic pump primer
- Adjustable flow control
- In-line sediment filter
- Quick connect hoses and tools
- Easy storage of accessories

	CTV-1501
Motor Power	1 1/2 HP
Input Power	Standard: 15 amps, 115V, 60 Hz AC Optional: 15 amps, 115V, 50 Hz; 7.5 amps, 230V, 60 Hz; or 7.5 amps, 230V, 50 Hz
Power Supply Cord	21', 14-3 GFCI
Static Water Lift	25'
Water Displacement	Variable, 0-60 GPM
Filtration	3/16" sediment capture
Pump	Centrifugal
Dimensions	35" high x 22" wide x 21" deep
Weight	125 lbs



ACCESSORIES:

CTV-EH-25: 25' vinyl crushproof extension hose Call for Price		
6225A: 36" extension tube	Call for Price	
6225-4A: 6" gulper tool	Call for Price	
6229A: 20" floor brush	Call for Price	
6225-3A: 12" paddle tool	Call for Price	
6228-HOSE-ASSY: 18" bulk pickup		
tool on hose extension	Call for Price	
6230A: 6" utility brush	Call for Price	

CTV-KIT-1501: TowerVac Accessory Kit 1 1/2": 25' vinyl crushproof extension hose, 36" extension tube, 20" floor brush, 12" paddle tool, 18" bulk pickup tool on hose extension, and 6" utility brush "**Call for Price**

Note: Call or visit website for additional accessories.



Call: 1-800-333-7467
Visit: www.goodway.com
Goodway Technologies Corporation

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com