DESIGNED BY EXPERTS IN DUCT CLEANING





FEATURES

 Portable and powerful - Little training required, single person operation

OPERATION

- Two-piece design comes apart easily - Easy cleaning and transportation
- Oversized wheels better mobility
- Reusable HEPA filtration save on filter costs
- 115v power connection -Convenient





FEATURES

- 3 stage filtrations:
 - 1. Cube Filter 381 mm X 381 mm X 101 mm
 - 2. Pleated air filter 406 mm X 406 mm X 50 mm. (Use to protect the HEPA Filter)
 - 3. HEPA Filter 99.97% 381 mm X 381 mm X 101 mm
- Aluminum with stainless steel accessories
- Lightweight
- Easy to Use

AQ-V-3M Duct Cleaning Vacuum— One-Person Operation

When you need a negative air pressure vacuum to clean ductwork, look no further than the AQ-V-3M high flow duct vacuum. This powerful 3,000-CFM negative air machine gives you the power of a duct truck in a portable format, quickly gobbles up dust, dirt, and debris agitated by duct cleaning.

The AQ-V-3M is designed by people who actually do duct cleaning. At just 22" in diameter, it fits through any doorway and it can break apart easily to get into tight spaces. The 12" wheels don't get caught up on stair treads so it's easy to get up and down stairs. The unique design works just as well upright or laying on its back.

Note: A dust mask and safety goggles must be worn when operating this equipment.

	AQ-V-3M
Input Power	Standard: 13.8 amps, 115V, 60 Hz AC
Power Supply Cord	50′
Suction	3200 CFM
Static Pressure	6.9"
Dimensions	60.25" high x 22" wide x 22" deep
Weight	125 lbs net dry

AQ-V-4A Duct Vacuum

The AQ-V-4A Duct Vacuum is the ultimate companion to the AQ-R1500 Duct Cleaner. This duct cleaning vacuum creates negative air pressure in air exchanger duct and small ductwork systems and captures the dust and other airborne debris quickly and safely. Easy to operate, this machine features 3 stages of filtration and includes a 254 mm x 3,9 m Flex Duct Hose.

AQ-V-4A: Duct Vacuum, including 254 mm x 3,9 m

Flex Duct Hose. Call for Price

Note: Call or visit website for specifications.

SPECIFICATIONS	AQ-V-4A
Motor Power	0,7 kW
Input Power	6 Amps, 115 V, 60 Hz AC Optional 6 Amps, 115 V, 50 Hz AC; 3 Amps, 230 V, 60 Hz AC; or 3 Amps, 230 V, 50 Hz AC
Power Supply Cord	6,5 m, 14-3 GFCI
Shaft Speed	Variable/Reversible 1.500 RPM
Shaft Feed Method	Manual
Shaft Length	Maximum 18,3 m
Special Features	Reversible Shaft Rotation
Dimensions	940 mm (H) x 510 mm (W) x 430 mm (D)
Weight	22 Kg, Net Dry



Call: 1-800-333-7467
Visit: www.goodway.com
Goodway Technologies Corporation

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com