WE'RE ABOUT TO MAKE YOUR JOB EASIER



BSL-50 - Reduces Fatigue

The BSL-50's air assisted trigger requires an incredible 90% less effort for firing projectiles – what a difference when you have thousands of tubes to clean! An easy-to-attach, padded aluminum shoulder stock provides added leverage when you need it. There's no bulky pressure gauge on the BSL-50.

The simple "cleared tube" indicator reliably shows when the projectile has exited the tube. But don't let all this comfort fool you, with a flow rate of up to 50 GPM, the BSL-50 Big Shot® cleans tubes faster than ever.

 $\textbf{Note:} \ \mathsf{Visit} \ \mathsf{goodway.com} \ \mathsf{for} \ \mathsf{projectiles.}$

FEATURES

- Versatile single or doublehanded use
- Rugged ABS exterior shell
- Air-assisted trigger
- Removable aluminum shoulder stock
- Compact, ergonomic design

- Easily interchangeable nozzles
- Clear, removable, high-density splash shield
- · Reliable cleared tube indicator
- Flow rate up to 50 GPM
- Internal vacuum break











REPLACEMENT SHIELD



BRASS TO RUBBER NOZZLE TIP

	BSL-50
Air Requirements	90-150 PSI at 1 CFM
Water Requirements	Maximum 600 PSI at 50 GPM
Dimensions	12" long (22" long with Shoulder Stock)
Weight	4 lbs (5 lbs with Shoulder Stock)
Carrying Case	14 1/2" high x 19" wide x 5 1/2" deep

OPTIONAL:

BSL-TIP: Replacement Nozzle Tip	Call for Price
BSL-OFFNOZ: 45° Nozzle	Call for Price
QA-1383: Replacement Shield	Call for Price
QSP-1212: Mesh Tarp, 12' high x 12' wide	Call for Price
TH: Tarp Holder, 5/8", 3/4", 7/8" or 1", 16-18 or 19-22 gauge (specify size)	Call for Price
BSL-1051-075087: Brass to rubber nozzle tip 3/4-16 thru 7/8 22 gauge	Call for Price
BSL-1051-087125: Brass to rubber nozzle tip 7/8-16 thru 1.25-22 gauge	Call for Price



Call: 1-800-333-7467
Visit: www.goodway.com
Goodway Technologies Corporation

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com