

A FASTER WAY TO A GREASE, GRIME AND GERM-FREE

PRODUCTION FACILITY



CE

GVC-18000 – Continuous Steam Power

The GVC-18000 dry steam cleaner is ideal cleaning equipment for food and beverage production facilities. The machine makes cleaning and sanitizing production and packaging equipment easier, all thanks to its powerful dry steam.

Our system delivers high pressure up to 145 PSI and heat up to 290° F to break down soils like fats, sugars, heavy buildup, and allergens on contact helping you to consistently deliver the results you need as part of your plant SSOPs. It also helps to kill yeast, mold, pathogenic bacteria, and other dangerous or spoilage microorganisms.

Plus, dry steam cleaning provides the benefit of targeted cleaning in dry environments, water sensitive equipment, hard to reach areas, and other challenging applications where traditional dry cleaning methods simply can't produce the results you need.

GVC-18000: Heavy-Duty Dry Steam Cleaner, including 33' hose with pistol grip, one-piece 20" wand with detail lance, one-piece 40" wand with detail lance, short detail lance, four 2 1/4" circular nylon brushes, four 2 1/4" circular brass brushes, four 2 1/4" circular stainless steel brushes, four 1 1/2" circular nylon brushes, four 1 1/2" circular brass brushes, four 1 1/2" circular stainless steel brushes, four circular nylon scrubbing brushes, four circular brass scrubbing brushes, four circular stainless steel scrubbing brushes, multi-brush tool, safety glasses, two chemical tanks and a 1 gallon bottle of cleaner.

Call for Price

Note: Call or visit goodway.com for additional accessories.

CUSTOMER FAVORITE



IDEAL FOR:

- Conveyor framework
- Chains
- Flow wrappers & baggers
- Diamond plate steps and catwalks
- Slicers
- Conveyor Belts (with automated attachments)
- Sandwich joints & niche areas
- Motors, conduit, electrical wiring

36,000 and 72,000 Watt units also available.

FEATURES

- Stainless steel construction
- Steam output at 7-9 gallons/hour (depending on moisture content)
- In operation refillable water tank
- Adjustable moisture content from 5-15%
- Continuous fill hose connection
- Four chemical-injection settings
- Stainless steel boilers and water tank
- Simultaneous vacuum option available Multiple cleaning tools
- Adjustable dry steam volume

GVC-18000	
Input Power	22 amps, 230V, 480V, 575V, 50/60 Hz AC, three phase Maximum 18-KW
Power Supply Cord	33', 10-4
Max. Output Steam Pressure	0 up to 145 PSI
Max. Output Steam Temperature	290° F
Boilers	Two 2.4 gallons stainless steel
Output Steam Volume	59 lbs/hr
Water Tank	10.4 gallons stainless steel
Chemical Tanks	Two 1.3 gallons
Dimensions	44" high x 28" wide x 41" deep
Weight	194 lbs net dry

GOODWAY®
INNOVATIVE MAINTENANCE SOLUTIONS

Call: 1-800-333-7467

Visit: www.goodway.com

Goodway Technologies Corporation

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com