

POWERFUL CLEANING AND SANITATION SOLUTION



GVC-6000 – Tough and Effective

The GVC-6000 Commercial Steam Cleaner is a portable and user-friendly solution for effective cleaning, sanitation, and disinfection in industrial settings. This 230V unit uses tap water to produce dry vapor steam, eliminating dirt, grease, bacteria, and grime with an adjustable pressure of 0-145 PSI and an output temperature of 320°F. The high steam temperature instantly removes oils, grease, and kills bacteria, viruses, mold, and other microorganisms, surpassing traditional chemical disinfectants in speed and efficiency. Plus, the low moisture content of the dry vapor steam, less than 10%, minimizes water residue and requires appropriate cleaning. The unit's chemical injection system enhances cleaning power, while the adjustable pressure ensures optimal visibility during surface cleaning. It is an ideal tool for commercial steam cleaning applications, including industrial equipment and product finishing. The unit comes with various cleaning tools and accessories for versatile use. Choose the GVC-6000 Commercial Steam Cleaner for superior performance in industrial cleaning.....**Call for Price**

FEATURES

- The GVC-6000 230V Commercial Steam Cleaner is a portable, easy-to-use solution for powerful cleaning, sanitation, and disinfection.
- It is designed for industrial cleaning.
- The unit produces dry vapor steam using standard tap water, with an adjustable pressure of 0-145 PSI and an output temperature of 320°F.
- It effectively removes dirt, grease, bacteria, and grime from surfaces.
- The high temperature of the steam kills bacteria, fungi, viruses, mold, mildew, and other microorganisms in just a few seconds.
- The unit's chemical injection system provides additional cleaning power.
- The adjustable pressure lets the operator release sufficient vapor steam to clean surfaces without reduced visibility.
- Three-phase power

GVC-6000-230V	
Input Power	13 amps, 230V, 60 Hz AC, three phase
Power Supply Cord	12'
Max. Output Steam Pressure	0 up to 145 PSI
Max. Output Steam Temperature	320° F
Boiler	0.95 gallon stainless steel
Output Steam Volume	19.5 lbs/hr
Water Tank	1.5 gallon stainless steel
Chemical Tanks	Two 1.3 gallons
Dimensions	40" high x 20" wide x 37" deep
Weight	72 lbs net dry



Call: 1-800-333-7467

Visit: www.goodway.com

Goodway Technologies Corporation

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com