

DOUBLE YOUR PERFORMANCE

WITH TWIN MOTORS



VAC-2 Increased Suction

The VAC-2 features dual-motors for increased suction. Its power and versatility make it an ideal choice for a wide range of general shop cleanup tasks, from liquid recovery to picking up metal shavings. With specially designed adapter rings, the VAC-2 is compatible with 15 gallon tanks or with 30 or 55 gallon drums to suit the size of the cleanup jobs you encounter.

A wide array of options and configurations are also available to suit your unique applications.

Note: Available with three motor and 230V configuration, call for VAC-3A pricing.

FEATURES

- Two heavy-duty motors
- Exhaust muffler
- Three tank sizes
- Liquid shut-off
- Metal deflector
- Reusable filters
- 1 1/2" or 2" hoses

ACCESSORIES

VAC-KIT-9: 1 1/2" Industrial Vacuum Accessory Kit: 10' Neoprene Wire Reinforced Hose, 54" Double Bend Wand, 54" Extension Tube, 5' Extension Tube, 14" Nylon Floor Brush, 14" Squeegee Floor Tool, 14" Rough Surface Fiber Shod Floor Tool, 8" Wall and Overhead Brush, and 27" Steel Crevice Tool..... **Call for Price**

DUMP VALVE (FACTORY INSTALLED)

DDV-100M: Full Flow Ball Valve, 1" **Call for Price**

DDV-E90: Elbow, 90° **Call for Price**

DDV-675: Garden Hose Connector **Call for Price**

STORAGE POUCH

VAC-TOOL-TOTE: Durabond Tool Storage Pouch..... **Call for Price**

REPLACEMENT FILTERS

GTC-175: Polypropylene Filter, 15 microns **Call for Price**

GTC-176: Dacron Filter, 15 microns **Call for Price**

DISCHARGE PUMP

The VAC-2-55-DD Industrial Vacuum is available with a 1/3 HP, 45 GPM, stainless steel internal pump for discharging recovered liquids.

VAC-2-55-PUMP: Same as VAC-2-55-DD, plus internal pump, discharge port and hose **Call for Price**



VAC-2-15SS



VAC-2-30-DD



VAC-2-55-DD



CE CERTIFICATION ONLY APPLIES TO VAC-2A 230V MODEL.

VAC-2-15SS: Industrial Wet-Dry Vacuum, including filters, 15 gallon stainless steel tank, handles, wheels and casters..... **Call for Price**

VAC-2-30*: Industrial Wet-Dry Vacuum, including filters and 18"-20" diameter drum adapter ring (no drum) **Call for Price**

VAC-2-30DD: Same as VAC-2-30, plus 30 gallon bonderized steel drum and dolly..... **Call for Price**

VAC-2-55*: Industrial Wet-Dry Vacuum, including filters and 22"-24" diameter drum adapter ring (no drum) **Call for Price**

VAC-2-55DD: Same as VAC-2-55, plus 55 gallon bonderized steel drum and dolly..... **Call for Price**

**Note: Fits any standard drum 30 or 55 gallon depending on model.*

Note: Vacuums do not include accessories. Order VAC-KIT-9, also shown on page 151, or individual accessories shown on pages 151-159.

| VAC-2 | |
|-------------------|---|
| Motor Power | 2.7 HP (total) |
| Input Power | Standard: 13 amps, 115V, 50/60 Hz AC Optional: 6.5 amps, 230V, 50/60 Hz |
| Power Supply Cord | 37', 14-3 |
| Static Water Lift | 66" |
| Air Displacement | 180 CFM |
| Filtration | 15 microns polypropylene and 15 microns Dacron |
| Tank/Drum | 15 gallons stainless steel tank, or 30 or 55 gallons bonderized steel drum |
| Dry Capacity | 14 gallons (stainless steel tank) |
| Wet Capacity | 10 gallons (stainless steel tank) |
| Noise Level | 74 dBA |
| Dimensions | 15" diameter tank x 36" high (VAC-2-15SS) |
| Weight | 25 lbs (head only) and 66 lbs (VAC-2-15SS) |

GOODWAY®
INNOVATIVE MAINTENANCE SOLUTIONS

1-800-333-7467

www.goodway.com

420 West Avenue, Stamford, CT 06902-6384 U.S.A. | 203-359-4708 | Fax: 203-359-9601 | goodway@goodway.com

Goodway is not responsible for typographical errors in product descriptions or pricing. Product availability and features may change. Actual products may differ slightly in appearance to images shown. Please contact Goodway with any questions prior to purchase. © Crossford International (2024) All Rights Reserved.