

THIS AIR VACUUM DOESN'T SKIMP ON POWER



AV-1200 Safe and Powerful

For situations when electric power is unavailable or prohibited, the Air-powered AV-1200 is the preferred choice. Maintenance departments all over count on this dependable vacuum.

With the ability to devour 45 gallons per minute, it handles all your high-volume liquid recovery needs. From machine oil to coolant and metal chips to fine powders, no matter what your clean up entails, the AV-1200 is up to the task.

AV-1200-15SS

AV-1200-30-DD

AV-1200-55-DD

FEATURES

- Air-powered
- No moving parts
- Three tank sizes
- Liquid shut-off
- Metal deflector
- Reusable filters
- 1 1/2" or 2" hoses



VAC-KIT-9-G

ACCESSORIES

VAC-KIT-9-G: 1 1/2" Grounded Industrial Vacuum Accessory Kit: 15' Neoprene Wire Reinforced Hose with Grounding Wire, 54" Double Bend Wand, 54" Extension Tube, 5' Extension Tube, 14" Nylon Floor Brush, 14" Squeegee Floor Tool, 14" Rough Surface Fiber Shod Floor Tool, 8" Wall and Overhead Brush, and 27" Steel Crevice Tool **Call for Price**

DUMP VALVE (FACTORY INSTALLED)

DDV-100M: Full Flow Ball Valve, 1" **Call for Price**

DDV-E90: Elbow, 90° **Call for Price**

DDV-675: Garden Hose Connector **Call for Price**

STORAGE POUCH

VAC-TOOL-TOTE: Durabond Tool Storage Pouch **Call for Price**

REPLACEMENT FILTERS

GTC-175: Polypropylene Filter, 15 microns... **Call for Price**

GTC-176: Dacron Filter, 15 microns **Call for Price**



AV-1200-15SS: Air-powered Wet-Dry Vacuum, including filters, 15 gallon stainless steel tank, handles, wheels and casters **Call for Price**

AV-1200-30*: Air-powered Wet-Dry Vacuum, including filters and 18"-20" diameter drum adapter ring (no drum). **Call for Price**

AV-1200-30-DD: Same as AV-1200-30, plus 30 gallon bonderized steel drum and dolly **Call for Price**

AV-1200-55*: Air-powered Wet-Dry Vacuum, including filters and 22"-24" diameter drum adapter ring (no drum) **Call for Price**

AV-1200-55-DD: Same as AV-1200-55, plus 55 gallon bonderized steel drum and dolly **Call for Price**

**Note: Fits any standard drum 30 or 55 gallon depending on model.*

Note: Vacuums do not include accessories. Order VAC-KIT-9, also shown on page 151, or individual accessories shown on pages 151-159.

AV-1200	
Air Requirements	Minimum 50 PSI at 35 CFM, Maximum 90 PSI at 50 CFM
Air Line	1/2" I.D. or larger
Static Water Lift	170" at 90 PSI
Air Displacement	125 CFM at 90 PSI
Filtration	15 microns polypropylene and 15 microns Dacron
Tank/Drum	15 gallons stainless steel tank, or 30 or 55 gallons bonderized steel drum
Dry Capacity	14 gallons (stainless steel tank)
Wet Capacity	10 gallons (stainless steel tank)
Noise Level	84 dBA
Dimensions	15" diameter tank x 36" high (AV-1200-15SS)
Weight	25 lbs (head only) and 66 lbs (VAC-2-15SS)

GOODWAY®
INNOVATIVE MAINTENANCE SOLUTIONS

1-800-333-7467

www.goodway.com

420 West Avenue, Stamford, CT 06902-6384 U.S.A. | 203-359-4708 | Fax: 203-359-9601 | goodway@goodway.com

Goodway is not responsible for typographical errors in product descriptions or pricing. Product availability and features may change. Actual products may differ slightly in appearance to images shown. Please contact Goodway with any questions prior to purchase. © Crossford International (2024) All Rights Reserved.