PORTABLY AND EFFECTIVELY REMOVE SCALE DEPOSITS



GDS-C92-FWF Innovative Flow Reversal and Fresh Water Flush

GDS-C92-FWF

CE

The updated GDS-C92-FWF is constructed of long-lasting, heavy-duty polyethylene and acid-proof components. Featuring the innovative flow reversal valve which eliminates the need to shut down and stop circulation to disconnect and change hoses, allowing for quicker and more effective scale removal. With an on-board tank that allows for foam and CO2 to be released, eliminating potential pockets, and speeding up the descaling process.

Now with the latest update, the freshwater flush, adds two additional ports, a freshwater inlet port and a flush or dump outlet port. These additional ports now provide operators a safe and seamless way to allow fresh water to be added, or discharge dumped without the removal of circulation hoses during the descaling process. Simply adjust your valving to the dump position, open the water inlet valve, and the flushing process begins. Clean, safe, simple.

The GDS-C92-FWF is a great option to use on mid-range equipment such as shell & tube heat exchangers or high efficiency package boilers.

FEATURES

- Acid proof pump and fittings
- Innovative flow reversal valve
- 21 GPM pump
- · Integrated fresh water flush
- Compact design for easy transport and storage
- 15 gallon reservoir tank
- · Venting cap for closed systems

GDS-C92-FWF APPLICATIONS

- Molds
- Extruders
- TCU's/Thermolators
- Steam generators
- Small package boilers
- Multistack/modular chillers
- · Small shell & Tube heat exchangers
- Brazed plate heat exchangers

GDS-C92-FWF: Scale Removal System, including 15 gallon tank and two 10' circulation hoses............ Call for Price Note: Chemical goggles must be worn when using this machine.

GDC-C92-FWF	
Motor Power	3/4 HP
Input Power	Standard: 8.6 amps, 115V, 60 Hz AC Optional: 4.3 amps, 230V, 50 Hz
Power Supply Cord	18′, 18-3
Output Water Flow	21 GPM
Pump	Centrifugal
Tank Capacity	15 gallons
Dimensions	35" high x 15" wide x 23" deep
Weight	50 lbs net dry





1-800-333-7467



www.goodway.com

BEST RESULTS - USE WITH SCALEBREAK®



GDS-MSA Adapters

Perfect for Cleaning Applications with Grooved Victaulic Fittings

These adapters are designed for systems utilizing grooved piping and come in:

1½" | 2" | 2½" | 3" | 4"

They are perfect for grooved connections on brazed plate heat exchangers and support our partnerships with Multistack, SWEP & WaterFurnace.



A set of two is required to attach to the top and bottom water supply. They are fitted with a ¾" male fitting and easily attach to both our GDS-C40 & GDS-C92-FWF pump systems. Simplify your next cleaning with these simple to use adapters.

- Quickly connect Goodway descaling systems to multistack, WaterFurnace and SWEP brazed plate heat exchangers
- Available in a variety of sizes
- High quality construction

GDS-MSA-200: Adapter for the GDS systems Call for Price

PH-PROBE-TESTER: Hand held electronic





BECOME A DESCALING EXPERT

SCALE: WHY YOU HAVE IT, WHAT IT DOES AND HOW TO DESCALE SAFELY AND EFFECTIVELY

To view the pre-recorded webinar visit the URL or scan the QR code:

Visit: goodway.com/goodway-scale-webinar







1-800-333-7467



www.goodway.com