

CLEANER TOWERS WITH ZERO DOWNTIME



CTV-1501 TowerVac® Efficiency with No Hassles



Safely remove cooling tower sediment sludge without having to drain or shut down the system. This award-winning product features an adjustable flow control that allows you to vacuum at a recovery rate of up to 60 GPM.

Easily remove slime, algae, mud, and other contaminants from the sides and floor of any cooling tower basin or sump. Stop dirty cooling tower water from fouling chillers, robbing efficiency, and increasing energy costs.

CTV-1501-60: TowerVac®, including 15' inlet and 25' outlet vinyl crushproof hoses, 48" wand, 6" gulper tool, and storage bag **Call For Price**

FEATURES

- Stainless steel construction
- Heavy-duty motor removes up to 60 gallons of water and debris per minute
- Semi-automatic pump primer
- Adjustable flow control
- In-line sediment filter
- Quick connect hoses and tools
- Easy storage of accessories

CTV-1501	
Motor Power	1 1/2 HP
Input Power	Standard: 15 amps, 115V, 60 Hz AC Optional: 15 amps, 115V, 50 Hz; 7.5 amps, 230V, 60 Hz; or 7.5 amps, 230V, 50 Hz
Power Supply Cord	21', 14-3 GFCI
Static Water Lift	25'
Water Displacement	Variable, 0-60 GPM
Filtration	3/16" sediment capture
Pump	Centrifugal
Dimensions	21" deep x 22" wide x 35" high
Weight	125 lbs



ACCESSORIES

- CTV-EH-25:** 25' vinyl crushproof extension hose.... **Call For Price**
- 6225A:** 36" extension tube **Call For Price**
- 6225-4A:** 6" gulper tool **Call For Price**
- 6229A:** 20" floor brush..... **Call For Price**
- 6225-3A:** 12" paddle tool **Call For Price**
- 6228A-HOSE-ASSY:** 18" bulk pickup tool on hose extension..... **Call For Price**
- 6230A:** 6" utility brush..... **Call For Price**

CTV-KIT-1501: TowerVac Accessory Kit 1 1/2": 25' vinyl crushproof extension hose, 36" extension tube, 20" floor brush, 12" paddle tool, 18" bulk pickup tool on hose extension, and 6" utility brush..... **Call For Price**

Note: Call or visit website for additional accessories.



1-800-333-7467

www.goodway.com

420 West Avenue, Stamford, CT 06902-6384 U.S.A. | 203-359-4708 | Fax: 203-359-9601 | goodway@goodway.com

Goodway is not responsible for typographical errors in product descriptions or pricing. Product availability and features may change. Actual products may differ slightly in appearance to images shown. Please contact Goodway with any questions prior to purchase. © Crossford International. All Rights Reserved.