

# CONTRACTOR SOLUTION FOR CLEANER TOWERS



## TFC-JR® Portable Cleaning Power

Designed for cleaning cooling tower fill, the TFC-JR is perfect for contractors and higher volume users. This small and lightweight chemical applicator is designed specifically to apply ScaleBreak®-Gel, our patented descaling gel, and BIOSPRAY®-Tower disinfectant.

It is pretty easy to use the product and requires minimal training. For descaling, all you need to do is attach the chemical siphon tube to the ScaleBreak-GEL container, connect the wands, and correct nozzles, and you can start applying. Let the solution rest over the tower for a while, and then clean it with our CC-400 and turbo nozzle combo.

When the TFC-JR is paired with the CC-400, it creates an innovative system that is used to remove scale deposits from cooling tower fill and other surfaces. Scale deposits are not only ugly to look at, but provide surface areas for bacteria, like Legionella, to flourish.

For disinfection, use the TFC-JR to quickly and evenly apply BIOSPRAY-Tower, which kills 99.9% of Legionella pneumophila when correctly applied to hard, nonporous surfaces like cooling towers.

## FEATURES

- Hand carried portable design
- Automated siphon for ScaleBreak-Gel and BIOSPRAY-Tower
- Extension wands and 25' hose for extra reach
- Integrated tool holder

**CC-400HFR-60:** HiFlo® Coil Cleaner, including 12' hose, spray gun, 3' sectional 3/8" diameter stainless steel condenser wand, 18" wand, turbo nozzles and two nozzles..... **Call For Price**

**TFC-JR:** Cooling Tower Fill Cleaning System, includes 25' of outlet hose, spray gun, three 24" stainless steel extension wands, foaming nozzle, 15° spray nozzle, dip tube, dip tube hose, 40° chemical nozzle, and a 45° quick connect adapter. .... **Call For Price**

**TFC-JR-A:** Cooling Tower Fill Cleaning System 230V/50HZ..... **Call For Price**  
*Note: Call or visit website for additional accessories.*

	TFC-JR	CC-400HFR
<b>Input Power</b>	Standard: 2 amps, 115 V, 50/60 Hz Optional: 2 amps, 230V, 50/60 Hz	Standard: 13 amps, 115V, 50Hz/60Hz Optional: 7 amps, 230V, 50Hz/60Hz
<b>Motor Power</b>	N/A	1 HP
<b>Power Supply Cord</b>	20', 14-3 GFCI	25', 14-3 GFCI
<b>Water Requirements</b>	Minimum 20 PSI at 2 GPM	Minimum 20 PSI at 3 GPM
<b>Output Water Pressure</b>	150 PSI	400 PSI
<b>Output Water Flow</b>	1.0 GPM	3 GPM
<b>Pump</b>	Water Pump	Axial
<b>Chemical Output Pressure</b>	200 PSI @ 60 Hz/150 PSI @ 50Hz	-
<b>Chemical Output</b>	0.5 GPM @ 60Hz/ 0.45 @ 50Hz	-
<b>Chemical Pump</b>	Positive Displacement Diaphragm	-
<b>Dimensions</b>	24" deep x 9.5" wide x 12" high	12" deep x 30" wide x 13" high
<b>Weight</b>	35 lbs net dry	45 lbs net dry

## RECOMMENDED CLEANERS



BIOSPRAY-TOWER



SCALEBREAK-GEL

**KILLS 99.9% OF  
LEGIONELLA**



1-800-333-7467

www.goodway.com

420 West Avenue, Stamford, CT 06902-6384 U.S.A. | 203-359-4708 | Fax: 203-359-9601 | goodway@goodway.com

Goodway is not responsible for typographical errors in product descriptions or pricing. Product availability and features may change. Actual products may differ slightly in appearance to images shown. Please contact Goodway with any questions prior to purchase. © Crossford International. All Rights Reserved.