

CONVERT FROM WASHER TO DRAIN CLEANER



GPW-1400 Adjustable and Powerful

Not only is the GPW-1400 powerful enough to tackle tough cleaning jobs, it's also one of our most versatile units with the capability to convert to a PulseJetter® Drain Cleaner in mere minutes. At 1,400 PSI, this high-pressure washer scours heavy-duty equipment with ease.

In pulse mode, it provides periodic bursts of power that effectively clear clogged floor drains. Power, versatility, mobility, durability—this two-in-one unit has it all!

FEATURES

- Heavy-duty construction
- 25' steel reinforced hose
- 3' stainless steel wand
- Variable pressure nozzle
- Can use hot water
- Locking casters
- Pressure Regulator
- Pulse Control

GPW-1400-60: Heavy-Duty Pressure Washer, including 36" wand, reel, 25' high-pressure hose, variable pressure nozzle and cart **Call for Price**

Note: See page 92 for accessories.



GPW-4000-G Max Flow

For situations where you don't have an electrical hookup, or any remotely located area, the gas-powered GPW-4000-G offers you flow while on the go. The 13 HP Honda engine on this all-purpose heavy-duty pressure washer burns clean, sips gas and runs smooth.

The engine is well balanced in its rugged cart, so you don't have to be a professional wrestler to transport it from job to job. With 4,000 PSI and 4 GPM, it's all the power and flow you'll need.

FEATURES

- 13 HP Honda engine
- Thermal valve to protect pump
- Safety pressure relief valve to protect operator
- 50' Steel reinforced hose
- 4' Plated steel wand
- Five color-coded quick connect nozzles
- Soap container
- Gasoline powered

GPW-4000-G: Gasoline Powered Pressure Washer, including 4' wand, 50' high-pressure hose, five quick connect nozzles, soap injector and cart **Call For Price**

Note: See page 92 for accessories.

	GPW-1400	GPW-4000-G
Motor Power	1 1/2 HP	13 HP Honda, recoil start
Input Power	Standard: 15 amps, 115V, 60 Hz AC; Optional: 15 amps, 115V, 50 Hz; 7.5 amps, 230V, 60 Hz; or 7.5 amps, 230V, 50 Hz	-
Power Supply Cord	37', 14-3 GFCI	-
Water Requirements	Minimum 25 PSI at 2 GPM	Minimum 25 PSI at 4.5 GPM
Output Water Pressure	Adjustable, 100-1,400 PSI	4,000 PSI
Output Water Flow	1.7 GPM	4 GPM
Pump	Triplex oil bath plunger	Triplex oil bath plunger
Dimensions	21" deep x 14" wide x 40" high	37" deep x 27" wide x 42" high
Weight	95 lbs net dry	140 lbs net dry

DRAIN CLEANER CONVERSION KIT



GPW-PJ-KIT: Drain Cleaner Conversion Kit, including 3/16" x 60' high-pressure hose and three jetter nozzles **Call For Price**

Note: For primary use as a drain cleaner see page 92.

GOODWAY[®]
INNOVATIVE MAINTENANCE SOLUTIONS

1-800-333-7467

www.goodway.com

420 West Avenue, Stamford, CT 06902-6384 U.S.A. | 203-359-4708 | Fax: 203-359-9601 | goodway@goodway.com

Goodway is not responsible for typographical errors in product descriptions or pricing. Product availability and features may change. Actual products may differ slightly in appearance to images shown. Please contact Goodway with any questions prior to purchase. © Crossford International. All Rights Reserved.